

# SJZ Metalsin Tech Co Ltd

## 4.1 Dimensions

DN		PN	Dimensions (mm)							
Inch	mm		L	H	D	D1	d	C	T	n-ΦL
2"	50	10/16	203	170	165	125	99	19	3	4-Φ19
2.5"	65	10/16	216	195	185	145	118	19	3	4-Φ19
3"	80	10/16	241	215	200	160	132	19	3	8-Φ19
4"	100	10/16	292	255	220	180	156	19	3	8-Φ19
5"	125	10/16	330	290	250	210	184	19	3	8-Φ19
6"	150	10/16	356	360	285	240	211	19	3	8-Φ23
8"	200	10	495	450	340	295	266	20	3	8-Φ23
		16	495		340	295	266	20	3	12-Φ23
10"	250	10	622	550	405	350	319	22	3	12-Φ23
		16	622		405	355	319	22	3	12-Φ28
12"	300	10	698	645	460	400	370	24.5	4	12-Φ23
		16	698		460	410	370	24.5	4	12-Φ28
14"	350	10	787	700	505	460	429	24.5	4	16-Φ23
		16	787		520	470	429	26.5	4	16-Φ28
16"	400	10	914	790	565	515	480	24.5	4	16-Φ28
		16	914		580	525	480	28	4	16-Φ31
18"	450	10	978	850	615	565	530	25.5	4	20-Φ28
		16	978		640	585	548	30	4	20-Φ31
20"	500	10	978	900	670	620	582	26.5	4	20-Φ28
		16	978		715	650	609	31.5	4	20-Φ34
24"	600	10	1295	1030	780	725	682	30	5	20-Φ31
		16	1295		840	770	720	36	5	20-Φ37

## 4.2 KV rates

<b>DN</b>	50	65	80	100	125	150	200	250	300	350	400	450	500	600
<b>Kv</b>	41	53	105	175	285	402	730	1160	1400	1770	3010	3225	3395	4272

Remote Float Valves for BS/ DIN/ EN waterworks systems.  
Flange dimensions to EN 1092-2 PN 10 & PN 16.

# SJZ Metalsin Tech Co Ltd

---

