

SJZ Metalsin Tech Co Ltd

DIN 3352 F4 Flanged Resilient OS&Y Gate Valve PN10/16

DN		PN	Dimensions(mm)									
Inch	mm		L	H1(Close)	H2(Open)	D	D1	d	C	T	M	n-ΦL
1.5"	40	10/16	140	323	373	150	110	84	19	3	180	4-Φ19
2"	50	10/16	150	323	373	165	125	99	19	3	180	4-Φ19
2.5"	65	10/16	170	343	408	185	145	118	19	3	180	4-Φ19
3"	80	10/16	180	370	450	200	160	132	19	3	200	8-Φ19
4"	100	10/16	190	442	542	220	180	156	19	3	254	8-Φ19
5"	125	10/16	200	540	665	250	210	184	19	3	280	8-Φ19
6"	150	10/16	210	608	758	285	240	211	19	3	305	8-Φ23
8"	200	10	230	720	920	340	295	266	20	3	350	8-Φ23
		16										12-Φ23
10"	250	10	250	940	1190	405	350	319	22	3	450	12-Φ23*
		16					355					12-Φ28
12"	300	10	270	1065	1365	460	400	370	24.5	4	450	12-Φ23
		16					410					12-Φ28
14"	350	10	290	1210	1560	520	460	429	26.5	4	500	16-Φ23
		16					470					16-Φ28
16"	400	10	310	1280	1680	580	515	480	28	4	500	16-Φ28
		16					525					16-Φ31
18"	450	10	330	1760	2210	640	565	530	30	4	650	20-Φ28
		16					585	548				20-Φ31
20"	500	10	350	1780	2280	715	620	582	31.5	4	650	20-Φ28
		16					650	609				20-Φ34
24"	600	10	390	1950	2550	840	725	682	36	5	720	20-Φ31
		16					770	720				20-Φ37